

PROSTAR™ LANCER™ Series CNC Cutting Systems Make Productivity Gains Affordable and Easy to Deploy



PROSTAR™ LANCER™ PRS51

Easily Deployable Cutting Systems

PROSTAR[™] LANCER[™] series CNC plasma cutting systems are an affordable solution for the steel processing needs of light fabricators, job shops, HVAC and sign companies—as well as artists and hobbyists.

With effective cut dimensions of $4' \times 8'$, $5' \times 10'$ or $6' \times 12'$, LANCER CNC cutting systems provide the ability to efficiently process carbon steel, stainless steel plate and more. These machines feature full support for HYPERTHERM® plasma systems, and FLASHCUTTM CNC controllers for fast cutting speeds, optimal nesting, exceptional cut quality and ease of use.

The LANCER PRS48, LANCER PRS51 and LANCER PRS62 CNC cutting systems require minimal setup and feature unitized frames that are forklift accessible, making them easy to deploy or move as facility needs evolve.

Applications

- → Light manufacturing
- → HVAC
- → Job shops
- → Sign shops
- → Artists / hobbyists


| Features | Benefits | | |
|--|--|--|--|
| 54 in. × 102 in. / 66 in. × 126 in. / 78 in. × 150 in. | Process carbon and stainless steel plate up to 6 ft. × | | |
| cut area | 12 ft. | | |
| Unitized frame | Easy to deploy and relocate to meet evolving needs | | |
| Available HYPERTHERM® plasma system or Oxy-Fuel | Exceptional cut quality – reduce time spent grinding | | |
| option | | | |
| Pierce cutting capacity | Plasma up to 1.25 in. (Oxy-fuel up to 3 in.) | | |
| FLASHCUT™ CNC controller | Easy setup, operation and nesting (CAD/CAM capable) | | |

Machine Specifications


| | PRS48 | PRS51 | PRS62 | |
|-------------------------------|--------------------------------|--------------|--------------|--|
| Traversing speed | Up to 700 IPM (servo driven) | | | |
| Cutting speed | Up to 325 IPM (Oxy-fuel 3 IPM) | | | |
| Pierce cutting capacity (in.) | 1-1/4 | | | |
| Cutting area width (in.) | 54 | 66 | 78 | |
| Cutting area length (in.) | 102 | 126 | 150 | |
| Dimensions (in.) | 71 W x 163 L | 83 W x 187 L | 95 W x 211 L | |
| Controller power requirement* | 20A/110V | | | |
| Drives power requirement* | 20A/240V (1/3ph) | | | |

^{*}Plasma cutting power source separate.





LANCER™ series PRS51



LANCER™ series PRS62



Cutting Systems

Available Plasma Linde's PROSTAR™ LANCER™ series CNC cutting systems can be configured with a number of HYPERTHERM® plasma cutting systems, as well as other manufacturers.

Available options include:

- → HYPERTHERM POWERMAX® Series (45, 65, 85, 105, & 125)
- → HYPERTHERM MAXPRO200®





Linde Inc.

10 Riverview Dr, Danbury, CT 06810, USA Phone 800.225.8247, www.lindedirect.com