

# Band Saws

Call Praxair to ask how we can help you increase productivity and lower your cost of operations.



## ProStar™ PRSBS613 Manual Band Saw



## Big Saw Power In a Smaller Saw Footprint

### STANDARD FEATURES

- 650 lbs.
- 7 in. × 13 in. capacity
- Cuts rounds to 7 in. or 6.5 in. at 45°
- Four-speed V belt drive
- 1 hp motor
- 3/4 in. blade
- 8 gallon wet cutting system is standard

*Available options include: casters, worklight, and roller conveyors.*

SPECIFICATIONS	PRSBS613
CAPACITY	6 in. × 13 in., rectangular 6 in. × 6-1/2 in. at 45°, 7 in. round, 13 in. flat
BLADE SIZE (H/W/L)	3/4 in × 0.35 in. × 99 in.
BLADE SPEED	50 - 90 - 160 - 250 sfpm
BLADE GUIDES	6 sealed ball bearings
BLADE TENSION	Manual <i>Rite Tension</i> ®
BLADE MOTOR	1 hp (1 ph) or (3 ph)
COOLANT TANK CAPACITY	8 gallons
WISE CONTROL	Manual screw/quick action
SWIVEL VISE	To 45°
FEED CONTROL	Hydraulic with adjustable counterbalance
BAND WHEELS	11 in. diameter cast iron
FOOTPRINT (W/L/H)	25 in. × 60 in. × 29 in.
SHIPPING WEIGHT	650 lbs.

### Available Options

### PART NO.

Variable speed blade drive (70-375 sfpm)	DL 613489
NFPA electrics (with disconnect)	DL613732
Work light	DL613781
Casters, set of 4 (2 locking)	100113003
Stock stand	098047001
5 ft. roller conveyor	098050006
10 ft. roller conveyor	098050007

Specifications subject to change without notice.  
Consult your Praxair representative when ordering.