## Manual Wet/Dry Band Saws





## ProStar™ PRSBS58B Portable Band Saws



SPECIFICATIONS	PRSBS58BD DRY CUTTING	PRSBS58BW WET CUTTING
CAPACITY	9-1/2 in. × 11 in., rectangular 5-1/2 in. × 5-1/2 in. at 45° 9-1/2 in. round, 11 in. flat	
THROAT DEPTH	6-1/4 in.	
THROAT HEIGHT	9-1/2 in.	
WORK TABLE (INCLUDED)	8 in. × 10 in.	
BLADE SIZE (H/W/L)	$1/2$ in $\times$ $1/4$ in. $\times$ 93 in.	
BLADE SPEED	76 - 141 - 268 sfpm	
BLADE GUIDES	6 sealed ball bearings on cast iron supports	
BLADE MOTOR	1/2 hp (1 ph) ODP	
VISE CONTROL	Manual screw/quick action	
SWIVEL VISE	To 45°	
BAND WHEELS	11 in. diameter cast iron	
FOOTPRINT (W/L)	26 in. × 54 in.	
58BD (DRY CUTTING)	350 lbs.	
58BW (WET CUTTING)	385 lbs.	

Specifications subject to change without notice. Consult your Praxair representative when ordering.

## Horizontal and Vertical Sawing

The *ProStar* PRSBS58B comes standard in either dry (PRSBS58BD) or wet (PRSBS58BW) configurations. This rugged machine features large capacity, is easily portable, and quickly converts from horizontal to vertical operation.

## STANDARD FEATURES

- 9-1/2 in. × 11 in. rectangles
- 5-1/2 in. × 5-1/2 in. at 45°
- Quickly converts to vertical sawing
- Work table included
- Full size gearbox
- 1/2 hp UL/CSA motor
- Cast iron bandwheels
- Made in U.S.A.

Available Options	DRY CUTTING/WET CUTTING
Spare blades pkg. (6)	PRSDL613781
3/4 in. spare blades pkg. (6)*	PRS100113003
Stock stand (wet or dry)	PRS098047001

<sup>\*</sup>Sawing capacity limited to 7 in. ×11 in. with this option.