

Ultra-Low Profile Turntables




ProStar™ Low Profile Turntables

Low-profile turntables are used for precise positioning in a flat or horizontal position. *ProStar* ultra-low profile turntables are among the lowest profile positioners on the market. They are available in any table size or capacity.



**LOADS UP TO
40 TONS**

PRSTRN10700



PRSTRN10400

SPECIFICATIONS	PRSTRN2LS300	PRSTRN2HS300	PRSTRN10700	PRSTRN10HS100	PRSTRN20200	PRSTRN40100
WEIGHT CAPACITY	2 tons	2 tons	10 tons	5,000 lbs. or 5 tons	20 tons	40 tons
ECCENTRICITY	Up to 4 in.	0 in. (high speed)	Up to 6 in.	0 in. (high speed)	Up to 6 in.	Up to 12 in.
SHIPPING DIMENSIONS	23.5 in. × 22 in. × 13.625 in.	23.5 in. × 22 in. × 13.625 in.	48.625 in. × 27.75 in. × 19.5 in.	36.75 in. × 36.75 in. × 21.375 in.	36.75 in. × 36.75 in. × 21.375 in.	120 in. × 120 in. × 44 in.
TABLE SIZE/SPAN	30 in.	30 in.	42 in.	52 in.	52 in.	120 in.
POWER REQUIREMENTS	110 V 1-ph	110 V 1-ph	110 V 1-ph	480 V 3-ph	480 V 3-ph	480 V 3-ph
ROTATION SPEED	0.1 rpm - 1.8 rpm	0.2 rpm - 10 rpm	0.1 rpm - 3.6 rpm	3-60 rmp/1.5 - 30 rpm	0.05 rpm - 1.5 rpm	0.05 rpm - 1.2 rpm
GROUND CAPACITY	800 A	800 A	800 A	800 A	1,500 A	1,500 A
SHIPPING WEIGHT	350 lbs.	400 lbs.	1,550 lbs.	1,900 lbs.	1,900 lbs.	12,350 lbs.
FORK LIFT POCKETS	Yes	Yes	Yes	Yes	Yes	Yes

Specifications subject to change without notice. Consult your Praxair representative when ordering.

Hand Pendants



PRSH100

Heavy rubber 25 ft. cable with 19-pin metal plug. Optional LCD readout. Wireless option available.

Foot Switches



PRSF5FR Forward/Reverse

Heavy-duty cast steel body with heavy-duty guard/handle and heavy rubber 25 ft. cable with 4-pin metal plugs.

ProStar™ Custom Turntables



Any style and table size up to 16 feet diameter. Capacity up to 100 tons. Any speed range or precision.